

## Tannoy Parts Price List

SIN #	Model	Product Description	GSA Price
58 4	8000-5640	Pre-installation Bracket for In-Wall Speakers	<b>\$78.11</b>
58 4	8000-5790	Retro Bracket for In-Wall Speakers	<b>\$119.46</b>
58 4	CMS6	Two-way extended range 6.5" Dual concentric driver mounted on a vented steel plate, designed for pre-install application with optional back can.	<b>\$215.94</b>
58 4	CMS6 TDC-60	Two-way extended range 6.5" Speaker 60W 70 Volt Dual Concentric driver, driver mounted on a vented steel plate, designed for pre-install applications with optional back can. 50W RMS/100W Program	<b>\$245.80</b>
58 4	CMS65 ICT-15	Two-way extended range 6.5" speaker 15W 70 Volt, driver mounted on a vented steel plate, designed for pre-install applications with optional back can. 50W RMS/100W Program	<b>\$102.23</b>
58 4	CMS65 ICT-4	Two-way extended range 6.5" speaker 4 ohm, driver mounted on a vented steel plate, designed for pre-install applications with optional back can. 50W RMS/100W Program	<b>\$78.11</b>
58 4	CMS65 ICT-60	Two-way extended range 6.5" speaker 60W 70 Volt, driver mounted on a vented steel plate, designed for pre-install applications with optional back can. 50W RMS/100W Program	<b>\$109.12</b>
58 4	CMS8	Two-way extended range 8" Dual concentric driver mounted on a vented steel plate, designed for pre-install application with optional back can.	<b>\$245.80</b>
58 4	CMS8-TDC-60	Two-way 8" Speaker 60W 70 Volt Dual Concentric driver mounted on a vented steel plate, designed for pre-install applications with optional back can. 90W RMS/180W Program	<b>\$274.52</b>
58 4	Definition iw210S	In-wall installation subwoofer using a 10" bass driver and 10" passive radiator in a painted MDF enclosure. 8ohm impedance, 250W RMS/500W program, 88dB sensitivity, -3dB @35Hz, -10dB @ 28HZ.	<b>\$775.31</b>
58 4	Definition iw60EFX	In-wall installation surround/effects speaker system using one 6.5" Dual Concentric driver and two 4" Dual Concentric drivers in a painted MDF enclosure. 8 Ohm impedance (depending on mode), 100W RMS/200W program, 90dB sensitivity, 110Hz-23kHz (+/-3dB).	<b>\$613.36</b>
58 4	Definition iw63 DC	In-wall installation two way speaker system using one 6.5" Dual Concentric driver and two 6.5" woofers in a painted MDF enclosure. 8 Ohm impedance, 100W RMS/200W program, 91dB sensitivity, 80Hz-28kHz (+/-3dB).	<b>\$575.46</b>
58 4	TEQ660	Tuned Back Can - Conduit Knockouts	<b>\$31.01</b>
58 4	TEQ660PL	TEQ660PL Tuned Back Can - With J-Box	<b>\$33.31</b>
58 4	TEQ880	Tuned Back Can - Conduit Knockouts	<b>\$44.80</b>
58 4	TEQ880PL	TEQ880PL Tuned Back Can - with J-Box	<b>\$50.54</b>
58 4	TGS 6/8	TRG 6/8 Square steel grille, White	<b>\$35.61</b>
58 4	TRG	6/8 Round Steel Grille, White	<b>\$13.78</b>
58 4	TTB	Tile Bridge for TEQ660 & TEQ880 Cans	<b>\$6.89</b>
58 4	V6 Black	Ultra Compact high performance speaker system with high power 6" Dual Concentric driver in trapezoidal MDF enclosure. 8ohm impedance, 100W RMS/200W program, 93dB sensitivity, 90Hz-22kHz (+/-3dB).	<b>\$412.35</b>

58 4	V6 White	Ultra Compact high performance speaker system with high power 6" Dual Concentric driver in trapezoidal MDF enclosure. 8ohm impedance, 100W RMS/200W program, 93dB sensitivity, 90Hz-22kHz (+/-3dB).	<b>\$412.35</b>
58 4	V8 Black	High performance two way speaker system using the 8" Dual Concentric driver. Birch plywood trapezoidal cabinet, 8ohm impedance, 130W RMS/260W program, 95 dB sensitivity, 85Hz-22kHz (+/-3dB).	<b>\$531.81</b>
58 4	V8 White	High performance two way speaker system using the 8" Dual Concentric driver. Birch plywood trapezoidal cabinet, 8ohm impedance, 130W RMS/260W program, 95 dB sensitivity, 85Hz-22kHz (+/-3dB).	<b>\$531.81</b>